# X SERIES MANURE SPREADERS

X700 & X900



# **Two Models to Spread Goodness on Your Farm or Ranch**

The X Series is meant to spread it wide and far with even field coverage. The amount needed depends on you and your operational needs. We have two models to choose from. Rest assured, the spray is smooth and even no matter how you cut it. Let's break it down:

- ▶ X700: 473 struck cu. ft. and 683 heaped cu. ft.
- ▶ X900: 625 struck cu. ft. and 909 heaped cu. ft.

# Simple to Fill

Easy loading is made possible by our flared sides and low loading heights of 92 in. on our X700 and 94 in. on our X900 with standard tires. Even better heights with our flotation tires, 89 in. on our X700 and 91 in. on our X900. The flared sides allow you to easily load material from the side over the wheel to decrease material loss and load time.



# Densilite floors

# 667XH chain

# **Used Military Tires**

X Series Spreaders feature tandem axles with 16 R-20 tires. These allow you to pull the load smoothly behind your tractor without taking the field out with you. What's more, 600/50 R 22.5 flotation tires are available for decreased soil compaction in your fields and lower loading weight.

# **Long Box Life**

Densilite floors have minimal thermal expansion and contraction for longer life.

Better yet, it creates a slick surface for enhanced material flow.

# Dependable

Our 667XH chain boasts a limited lifetime warranty so you know you are always covered while in used. With 31,000 lb. of tinsel strength per chain, carry your material towards or away from the beaters. Robust tube steel slats provide additional durability while moving more and more manure.













# **Transport Safety**

Bright LED lights, a strong safety chain and a convenient 2-speed heavy-duty jack make you more visible and secure on the road.

Move manure wisely.

# **Operator Protection**

A heavy-duty rock guard is mounted on the front for maximum protection. Because safety is a front and back proposition.

# **Operator Convenience**

Slip resistance and color-coded hydraulic grips make hooking up a breeze. A bolt tensioning system allows for in-the-field chain adjustment. Grease points maintain smooth machine operation and can be easily accessed.

# **Common Components**


Service your spreader with quality Art's Way replacement parts that come in black for installation on any color box.

# **Even Spread Pattern**

The guillotine style slop gate precisely controls how the material enters vertical beaters. Hydraulic cylinders operate the gate up and down. Combined with two powerful beaters, this creates fewer clumps in your field and smooth even coverage. The key is the angle of the beaters and how the floor feeds into them.



# **X Series Spreader Options**







# Scale system

# **Heavy-Duty Slats**

The same strong tube steel slats just got better. This option features a 36% increase in tube wall thickness to move even the harshest of material.

#### **Litter Paddle Kit**

Art's Way beaters get even better with our litter paddle kit. This option allows you to maintain a more consistent spread pattern with even the finest materials.

#### **Harden Beater Teeth Kit**

An optional kit with hardened teeth gives you extended life on your machine. The weld is hardened 0.5 in. on the steel teeth with thick reversible knives.

# **Scale Systems**

A scale option to meet the needs of any operation. Monitor your load weight and application poundage with the GT400 indicator on NT560 Indicator. Get precise flow control with the complete Raven System.

# **Flotation Tires**

Creates less field compaction and utilize a lower loading height when you choose the flotation tires instead of our standard used military tires.



# **GT400 Digi-Star Indicator**

- Basic scale functions
- Easy to calibrate
- · Economic decision



# NT560 Digi-Star Indicator

- Advanced scale functions
- Auto Log Feature
- GPS and record documentation
- · Live application rate readout
- · USB stick and software for data transfer
- Ton per acre or pounds per acre



### **Raven Rate Control Module**

- ISOBUS compatible
- Automated rate application
- Uses existing load cells
- · Intuitive user interface
- Expandable option for multi-product
- On-screen configuration



### **Raven CR7 Monitor**

- ISOBUS compatible
- GPS included (500S antenna)
- 7 in. full touch screen
- Slingshot compatible (file transfer)
- Raven Auto Steer supported

	X700	X900
Box length	18 ft.	20 ft.
Overall length	27 ft. 8 in.	30 ft. 11 in.
Overall width (with tires)	11 ft. 1.5 in.	11 ft. 5.5 in.
Overall height	9 ft. 10 in.	10 in.
Load height	7 ft. 8 in.	7 ft. 10 in.
Capacity - heaped	683 cu. ft.	909 cu. ft.
Capacity - struck	473 cu. ft.	625 cu. ft.
Empty weight	12,200 lb.	16,800 lb.
Inside width of box	6 ft.	6 ft.
Inside height of box	4 ft. 3 in.	4 ft. 8 in.
Flared sides	1 ft. 4 in. 45°	1 ft. 45°
Apron chain	667XH	667XH
Floor material	1/2 in. Densilite	1/2 in. Densilite
Reversible apron	Yes	Yes
Pintle hitch	2 in.	2 in.
Gear drive	Double 350 gear drive	Double 350 gear drive
Axles	Tandem	Tandem
Tires	16.00/R-20	16.00/R-20
Flotation tires (optional)	660/65R 22.5	660/65R 22.5
CV PTO	Optional	Optional
Slop gate cylinders	Chief	Prince
Vertical beaters	SRT8 removable	SRT8 removable
Power requirement	120-150 hp	180-200 hp
Shipping dimensions	8 ft. 5 in. x 28 ft. x 9 ft. 10 in.	8 ft. 5 in. x 32 ft. x 10 in.

Art said it best: "we may be around muck all day, but we don't muck around."

**Art's Way: How Work Gets Done.** 



Want to watch it work? See the manure spreaders in action by scanning the QR code below.



Get your hard work done with Art's Way — contact your nearest dealer today.

(712) 208-8467 | artsway.com









